

OVERVIEW

CLEXOCLEAR-COAT is an elastic, transparent acrylic UV TRP that provides resistance to weathering, and foot traffic and offers UV and weathering properties. They give glossy finish with enhance the color of the substrate. It waterproofs the concrete and other absorbent very effectively.

PROPERTITES

- Excellent coating for exterior brick tiles, dhollpur marble and other stones.
- Crack bridging ability.
- Clear transparent coating.
- Easy to apply
- Elastic coating
- Glossy finish
- Waterproofing properties
- Block all the pores, prevent water penetration through capillary action.

AREAS OF USES

- CLEXOCLEAR-COAT is a excellent waterproofer for:
Terraces,
Roofs,
Parapet walls,
Wood,
Exterior and interior walls etc.
- Waterproofing of all types tiles like mosaic, dhollpur and marbles chips tiles where the aesthetic color value restention is of prime importance.
- An as anti-corrosive primer for metal surface, steel structures, G.I sheets, Pipes, Machinery etc

INSTRUCTIONS FOR USE

The application temperature should be between 5°C to 45°C. Application procedures may vary slightly depending upon site conditions. The general recommended guidelines for the application of the waterproofing system are as follows:

SURFACE PREPARATION

The surface shall be cleaned thoroughly of all contaminants like dust, traces of curing compound, oil and grease. All surface imperfections and protrusions shall be removed and repaired.



CLEXOCLEAR-COAT (TRANSPARENT / CLEAR WATERPROOFING COATING) CECPL-1011

First of all the surface must be prepared properly. The entire surface must be clean, free from dirt, grease, oil and other loose particles. Fill the visible cracks, joints and gaps with crack filler. Allow it to cure for 24 hrs., Observe the filled area, if required fill the cracks once again to the level of the surface. Mix the container well and apply one coat of **CLEXOCLEAR-COAT** on the prepared surface, allow it to dry for 4-6 hours. Apply the 2nd coat of **CLEXOCLEAR-COAT**. If subsequent coats are required then apply at an interval of 6 hours. It is recommended to apply **CLEXOCLEAR-COAT** on a bone dry surface. Paint can be applied as a topcoat over **CLEXOCLEAR-COAT** coating directly.

COVERAGE:-

The coverage depends on the type of the surface.

First coat ... smooth surface 50-60 sqft

Second coat... smooth surface 55-65 sqft

PRECAUTION:

Mix only the required quantity of material, which can be utilized within stipulated pot life to avoid solidification.

Wash all the tools and tackles with industrial solvent immediately after the application is completed.

HEALTH & SAFETY

As with all chemicals, caution should always be exercised. avoid prolonged contact with eyes and skin. Protective clothing such as gloves and goggles should be worn. See the relevant material safety data sheet for more information.

PACKING & STORAGE

CLEXOCLEAR-COAT is available in 20kg plastic pails. Shelf life is 12 months in unopened container. store containers in a clean dry area protected from direct Sunlight and extreme heat and cold.

For further details visit: www.clexoengineering.com

October 2022 – Issued by CLEXO Technical Centre,

We are driving Waterproofing administrations supplier and waterproofing workers for hire in India. We give 5 and 10 years guarantee (relies upon the material quality) on our all administrations including new and old administrations from us.

CLEXO ENGINEERING & CHEMICALS PVT. LTD. has remained an expert waterproofing administrations worker for hire on both new developments



CLEXO
Life of Construction

CLEXOCLEAR-COAT

(TRANSPARENT / CLEAR WATERPROOFING
COATING)
CECPL-1011

PICTURES/IMAGES AT GLANCE



CLEXO ENGINEERING & CHEMICALS PVT. LTD



[An ISO 9001: 2015 Company]

SEC-C2, PLOT C-35, KASHMIRI ENCLAVE

TRONICA CITY GHAZIABAD -201102

CONTACT AT: +91-8266929206, +91-9990429206

Website: www.clexoengineering.com Email: clexoengineering@gmail.com

For further details visit: www.clexoengineering.com

October 2022 – Issued by CLEXO Technical Centre,

We are driving Waterproofing administrations supplier and waterproofing workers for hire in India. We give 5 and 10 years guarantee (relies upon the material quality) on our all administrations including new and old administrations from us.

CLEXO ENGINEERING & CHEMICALS PVT. LTD. has remained an expert waterproofing administrations worker for hire on both new developments